



TECHNICAL DATA SHEET.

TECHNICAL MULTI-PURPOSE SPRAY.

■ PRODUCT OVERVIEW

Multilubricant, deblocking spray.

Formulated with synthetic oils, special solvents and corrosion protectors, to which is added the unique TETRALUBE antifriction's additive.

Highly penetrating and lubricating properties.

Excellent moisture displacer, reaching the most inaccessible places.

Lubricates and protects against corrosion.

Has a very low surface tension ensures excellent penetration.

■ UTILITY

Breaks loose rusted joints & bolts.

Controls rust and corrosion.

Removes noise and squeaks.

Lubricates and protects against corrosion and moisture.

Cleans and dissolves greases.

Removes and protects from moisture with dielectric properties.

Indispensable general industries

Garage Workshops

In the lubricating construction rules springs, wires, braces, etc.

Chains and stiff bearings.

Shafts wagons

Shipbuilding, rail and aviation.

■ TYPICAL PHYSICAL PROPERTIES

Appearance:	Clear liquid.
Color:	Soft green.
Odor:	Characteristic.
D:	-0020 + 0810 gr / cc.

■ APPLICATION

How to use:

1. Shake the can before use.
2. Spray from a distance of 20-30 cm. of surfaces or parts to be treated.
3. In cases of extreme difficulty, wait and repeat.
4. For pieces or areas of difficult access, use the tube extender.

Caution: *Excessive application does not improve product performance.*

■ PACKAGING

TETRALUBE's Technical multi-purpose spray is supplied in 400 ml aerosol can.

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. This guideline has been technically revised; all previous versions are invalid.